

## 4KS - European profile | Double cylinder SYMO DZ



### Product description

The 4KS European profile double cylinder with modular design (SYMO) is suitable for indoor and outdoor use. The cylinder features external key override. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

### Technical information SE

Cylinder length on the outside A in mm	27   31   36   41   46   +5 ...   A + B ≥ 62 mm
Cylinder length on the inside B in mm	27   31   36   41   46   +5 ...   A + B ≥ 62 mm
Finish	NI – Nickel   MS – Brass satin   NP – Nickel front polished   NPV – Nickel fully polished   MP – Brass front polished and coated   MPV – Brass fully polished and coated   ML – Brass coated   CR – Chrome   CP – Chrome front polished   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional security features	ARS – Snapping protection   AS-A – Outside anti-snap option   FZG – Free wheel cam for geared lock   KZS – Plug pulling/drilling protection   SKG3-[A, I, B] – Certified SKG 3 lock cylinder*   VDS – Certified VdS lock cylinder   VDSBZ+ – Certified VdS-BZ+ lock cylinder
Options – Technical installation position	BIF – Biffar® double cam   BLIND – Blind cylinder   SEW – Sea water resistance   ZR14 – Cog wheel cam (14 teeth)   ZVS – Cylinder with shortened body   SSW – Protection against dust and weather conditions
Usage characteristics options	BSZ – External key override   NS – Nickel silver plug   TXT – Customer-specific numbering
Security features	Unlocking authorisation verification in a minimum of 18 verification positions (authorisation positions)   12 springless, linear-control locking sliders   Different steel elements made of hardened metal and hardened steel as drilling and plug pulling protection   Durable and resistant Nirosta linking axis as twisting and snapping protection
Standards and guidelines	EN 1303:2015 160B0C6D   Austrian standard B5351: WZ6-BZ6-BZ   EN1627   VdS BZ(+) option   VdS option***   SKG option***   BSI option***
Technical installation situation	For mortise locks as per DIN, Austrian standard and screw-on locks suitable for the installation of European profile lock cylinders   Cam width 9.3 mm
Included components	Lock cylinder with M5 fastening screw



### Dimensional drawing

